

TO-92 Plastic-Encapsulate Transistors


FEATURES

- High Voltage
- Complement to BC556,BC557,BC558
- TRANSISTOR (NPN)

MECHANICAL DATA

- Case style:TO-92molded plastic
- Mounting position:any

TO-92



MAXIMUM RATINGS AND CHARACTERISTICS

@ 25°C Ambient Temperature (unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{CBO}	Collector-Base Voltage	BC546	80	V
		BC547	50	
		BC548	30	
V_{CEO}	Collector-Emitter Voltage	BC546	65	V
		BC547	45	
		BC548	30	
V_{EBO}	Emitter-Base Voltage	BC546	6	V
		BC547	6	V
		BC548	5	V
I_C	Collector Current-Continuous		0.1	A
P_C	Collector Power Dissipation		625	mW
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient		200	°C/W
T_j	Junction Temperature		150	°C
T_{sta}	Storage Temperature		-55~+150	°C

ELECTRICAL CHARACTERISTICS (T_a=25°C unless otherwise specified)

Parameter		Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	BC546	$V_{(BR)CBO}$	$I_C = 0.1\text{mA}, I_E = 0$	80			V
	BC547			50			
	BC548			30			
Collector-emitter breakdown voltage	BC546	$V_{(BR)CEO}$	$I_C = 1\text{mA}, I_B = 0$	65			V
	BC547			45			
	BC548			30			
Emitter-base breakdown voltage	BC546	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}, I_C = 0$	6			V
	BC547			6			
	BC548			5			
Collector cut-off current	BC546	I_{CBO}	$V_{CB} = 70\text{V}, I_E = 0$			0.1	μA
	BC547		$V_{CB} = 50\text{V}, I_E = 0$			0.1	μA
	BC548		$V_{CB} = 30\text{V}, I_E = 0$			0.1	μA
Collector cut-off current	BC546	I_{CEO}	$V_{CE} = 60\text{V}, I_B = 0$			0.1	μA
	BC547		$V_{CE} = 45\text{V}, I_B = 0$			0.1	μA
	BC548		$V_{CE} = 30\text{V}, I_B = 0$			0.1	μA
Emitter cut-off current		I_{EBO}	$V_{EB} = 5\text{V}, I_C = 0$			0.1	μA
DC current gain		h_{FE}^*	$V_{CE} = 5\text{V}, I_C = 2\text{mA}$	110		800	
Collector-emitter saturation voltage		$V_{CE(sat)}$	$I_C = 100\text{mA}, I_B = 5\text{mA}$			0.3	V
Base-emitter saturation voltage		$V_{BE(sat)}$	$I_C = 100\text{mA}, I_B = 5\text{mA}$			1.1	V
Base-emitter voltage		V_{BE}	$V_{CE} = 5\text{V}, I_C = 2\text{mA}$	0.58		0.7	V
			$V_{CE} = 5\text{V}, I_C = 10\text{mA}$			0.75	V
Collector output capacitance		C_{ob}	$V_{CB} = 10\text{V}, I_E = 0, f = 1\text{MHz}$			4.5	pF
Transition frequency		f_T	$V_{CE} = 5\text{V}, I_C = 10\text{mA}, f = 100\text{MHz}$	150			MH

CLASSIFICATION of h_{FE}

RANK	A	B	C
RANGE	110-220	200-450	420-800